

VTKIPKIT3S

DAHUA IP Intercom Kit VTO6210B -VTH1510CH Surface Mount



Related Products



DHPFM111
DAHUA Micro SD card Class 10, 32GB



DHPFM110
DAHUA Micro SD card Class 10, 16GB

Description

7 Inch IP 1 door Kit IP Villa Outdoor Station HD CMOS camera. Tempered glass panel, IP65. Night vision & Voice indication. Video & Audio messaging. Remote intercom with mobile APP. Surface mounted. IP Indoor Monitor 7" TFT Resistive touch screen. IPC surveillance. Alarm integration. Micro SD card optional, max 32GB. Record & Snapshot (SD card needed).

Features

Video Outdoor Station	
Model	VTO6210B
System	
Main Processor	Embedded Micro Processor
Operation System	Embedded LINUX OS
Video	
Video	H.264
Compression	H.264
Image Sensor	1/4" 1MP CMOS
Lens	3.6mm
Angle of View	D:70° H:60°
Day/Night	Color Image
Audio	
Audio	G.711
Compression	G.711
Audio Input	Omnidirectional Mic
Audio Output	Built-in Speaker
Bidirectional Talk	Support Dual-way Bidirectional talk
Operation Mode	
Keypad	Single Touch Button
Reader	Mifare Card
Interface	
Door Control	2(1 relay out for main lock, 1 extended by access control module)
Alarm In	2(1ch unlock button, 1ch feedback)
RS485	1
Network	
Ethernet	10M/100Mbps Self-adaptive
Network Protocol	TCP/IP
General	
Ingress Protection	IP65
Tamper Switch	1
Installation	Surface
Material	Tempered Glass
Power	DC 12V
Power Consumption	Standby ≤1W, Work ≤10W
Working Temperature	□30°C~+60°C
Relative Humidity	10%~90%RH
Dimensions	154.2mm×114.2mm×43.0mm

Weight	0.6Kg
Video Indoor Monitor	
Model	VTH1510CH
System	
Main Processor	Embedded Micro Processor
Operation System	Embedded LINUX OS
Video	
Video Compression	H.264
Audio	
Audio Compression	G.711
Audio Input	All-direction Microphone
Audio Output	Built-in Loudspeaker
Bidirectional Talk	Support Dual-way Bidirectional talk
Display	
LCD Screen	7" 800x480, Resistive
Operation Mode	
Input	Touch buttons
Interface	
Alarm In	6
Alarm Out	1
RS485	1
Network	
Ethernet	10M/100Mbps Self-adaptive
Network Protocol	TCP/IP
General	
Memory Slot	Micro SD, Max 32GB
Installation	Surface
Power	DC 12V/ supply directly by VTNS1060A
Power Consumption	Standby ≤1.5W, Work ≤7W
Working Temperature	□10°C~+55°C
Relative Humidity	10%~90%RH
Dimensions	200.5mm×136.5mm×22.0mm
Weight	0.8Kg

CABLETECS

Contact Details

Cabletecs
30 Rose Crescent
McLaren Flat SA 5171

0404 610 900